












SIMPSON STRONG-TIE® COMPANY, INC.

12246 Holly St., Riverside CA 92509
 Telephone: 800-999-5099 • Facsimile: 951-369-2889

SIMPSON STRONG-TIE® CURTAIN WALL CLIPS AND BRIDGING CLIPS **as of 03/11/15**

Application	Drawing	Nominal Size/Length/Notes	Model No.	ClarkDietrich X-Ref	TSN X-Ref	Marino X-Ref
By-Pass Slide Clip	 SCB45.5	3½" (16ga.)	SCB43.5-KT	FCSC 3.5	SLB362	WSC362
		5½" (16ga.)	SCB45.5-KT	FCSC5.5, FCEC6	SLB600	WSC600
		5½" (14ga.)	MSCB45.5-KT	FCSC5.5, FCEC6	SLB600	WSC600
		7½" (16ga.)	SCB47.5-KT	FCEC8	SLB800	WSC800
		7½" (14ga.)	MSCB47.5-KT	FCEC8	SLB800	WSC800
		9½" (16ga.)	SCB49.5-KT	FCEC10	SLB1000	WSC1000
		11½" (16ga.)	SCB411.5-KT	FCEC12	SLB1200	WSC1200
By-Pass Slide Clip Strut	 SSB3.518	18" (16ga.)	SSB3.518-KT	FS12, FS15	SLS362-9 SLS600-12 SLS600-15 SLS600-18 SLS800-12 SLS800-15	OUTRIGGER
Head-of_Wall Slide-Clip	 SCW5.5	3¼" (16ga.)	SCW3.25-KT	FTC3	VTD362 VTX362 SLD362 SL362	3T1000
		5½" (16ga.)	SCW5.5-KT	FTC5	VTD600 VTX600 SLD600 SL362	6T1000
Shouldered Screw		3/4"	XSH34B1414-RP83	NA	NA	NA
By-Pass Fixed-Clip	 FCB45.5	3½" (16ga.)	FCB43.5-R25	UCEC	LB362	WRC362
		5½" (16ga.)	FCB45.5-R25	UXRC6	LB600	WRC600
		7½" (16ga.)	FCB47.5-R25	UXRC8	LB800	WRC800
		9½" (16ga.)	FCB49.5-R25	UXRC10	LB1000	WRC1000
		11½" (16ga.)	FCB411.5-R25	UXRC12	LB1200	WRC1200
Load Bearing Bridging Clips		3¼" - 8" Studs 20 16ga. (20ga. Clip)	LSUBH3.25-R150	FB43 SPAZZER5400	BRIDGECLIP BC600 BC800	NA
		3¼" - 8" Studs 20 16ga. (18ga. Clip)	SUBH3.25-R150	FB43 SPAZZER5400	BRIDGECLIP BC600 BC800	NA
		3¼" - 8" Studs 16 12ga. (14ga. Clip)	MSUBH3.25-R100	FB68 SPAZZER5400	BRIDGECLIP BC600 BC800	NA
Non-Load Bearing Bridging Clips		3¾" - 6" 20 25ga Studs	DBC2.5-R200	SPAZZER 9200	BRIDGE CLIP	NA
90 Degree Utility Clips (16 ga.)	 L90	3"	L30			
		5"	L50			
		7"	L70			
		9"	L90			
Skewable Utility Clips (18 ga.)	 S/LS	5"	S/LS50			
		7"	S/LS70			

1) Note that dimensions of x-reference parts will rarely be an exact match and that this could cause an issue with substituting one product for another. Gauges of x-reference parts may vary as well.
 2) Because of the above notes, as well as other considerations, it is the responsibility of the Installer and Designer to determine if the Simpson Connector is adequate for the intended application.



SIMPSON STRONG-TIE® COMPANY, INC.

12246 Holly St., Riverside CA 92509
 Telephone: 800-999-5099 • Facsimile: 951-369-2889

SIMPSON STRONG-TIE® UTILITY CLIPS **as of 3/11/15**

Application	Drawing	Nominal Size/Length/Notes	Model No.	ClarkDietrich X-Ref	TSN X-Ref	Marino X-Ref
Joist Clips		2" x 4-1/2" x 10-1/4" (14ga.)	SJC10.25-R15	LS541 LS681 E541 E681 S541 S681 X541 X681	JC1200-68 JC1200-43 JC1400-68 JC1600-68 JH1200-68	UA1112 UA1312 UA1412 UA2212 (16 AND 14GA)
		2" x 4-1/2" x 10-1/4" (12ga.)	MSJC10.25-R15	LS971 E971 S971	JH1200-97 JC1200-68	UA1112 UA2212 UA1312 (12GA)
		2" x 4-1/2" x 8-1/4" (14ga.)	SJC8.25-R15	LS549 LS689 E549 E689 S549 S689 X549 X689	JC1000-68 JH1000-68	UA119 UA1110 UA229 UA2210 UA139 UA1310 UA149 UA1410 (16&14ga.)
		2" x 4-1/2" x 8-1/4" (12ga.)	MSJC8.25-R15	LS979 E979 S979 X979	JH1000-97	UA119 UA1110 UA229 UA2210 UA139 UA1310 UA149 UA1410 (12ga.)
Stud Clips		1-3/8 " x 4" x 6-1/4" (16ga.)	LSSC6.25-R30	LE547 LA547 E547	JH800-43 JC800-43	UA138 UA148 LA338 (16GA.)
		1-3/8 " x 4" x 6-1/4" (14ga.)	SSC6.25-R30	LE687 LA687 LS687 E687 U687 B687 X687	JH800-68 JC800-68 AL800	UA138 UA148 UA338 (14GA.)
		1-3/8 " x 4" x 6-1/4" (12ga.)	MSSC6.25-R30	LE977 LA977 LS977 E977 U977 B977 X977		UA118 UA228 UA138 UA148 LA338 (12GA.)
		1-3/8 " x 4" x 4-1/4" (16ga.)	LSSC4.25-R50	LE545 E545 A546	JH600-43	UA135 UA145 LA335 (16GA.)
		1-3/8 " x 4" x 4-1/4" (14ga.)	SSC4.25-R50	UCEC UXRC6 LE685 LA685 E685 A686	LB600 LB-HD AL600	UA135 UA145 LA335 (14GA.)
		1-3/8 " x 4" x 4-1/4" (12ga.)	MSSC4.25-R50	UCEC LE975 LA975 E975 U975 X975 B975 A976		UA115 UA225 UA135 UA145 LA335 (12GA.)
			2-1/4" x3" x 2-1/4" (14ga.)	SSC2.25-R125	LE543 LE683 LA543 LA683 E543 E683 A543 A683	AL362 JH362 43 JC362-43
2-1/4" x3" x 2-1/4" (12ga.)	MSSC2.25-R90		LS973 LE973 LA973 S973 E973 U973 B973 X973 A973	LB362 JH362 68 JC362-68	UA113 UA223 UA133 UA143 LA333 (12GA.)	
Framing Clips		1-1/2 x 1-3/4 x 6-1/4 (18ga.)	LSFC6.25-R125	NA	NA	NA
		1-1/2 x 1-3/4 x 6-1/4 (16ga.)	SFC6.25-R100	LS547 S547 B547 U547 X548	NA	UA118 UA228 UA138 (16GA.)
		1-1/2 x 1-3/4 x 4-1/4 (18ga.)	LSFC4.25-R175	NA	NA	NA
		1-1/2 x 1-3/4 x 4-1/4 (16ga.)	SFC4.25-R175	LS545 S545 B545 U545 X545	NA	UA115 UA225 UA135 BRC6 (16GA.)
		7/8" x 1-3/4" x 2-1/4" (18ga.)	LSFC2.25-R300	NA	NA	NA
		7/8" x 1-3/4" x 2-1/4" (16ga.)	SFC2.25-R300	LS543 S543 B543 U543 X543	NA	UA113 UA223 UA133 BRC3
Knee Wall Clips		1-3/8 " x 4" x 4-1/4" (12ga.) with 1/2" x 3" Bearing Plate	MSSC4.25KW-KT20	D686 D976 T686 T976	CL600-68 CL600-118	RCC600
		1-3/8 " x 4" x 6-1/4" (12ga.) with 1/2" x 3" Bearing Plate	MSSC6.25KW-KT20	NA	CL800-68 CL800-118	RCC800

1) Note that dimensions of x-reference parts will rarely be an exact match and that this could cause an issue with substituting one product for another.

Gauges of x-reference parts may vary as well.

2) Because of the above notes, as well as other considerations, it is the responsibility of the Installer and Designer to determine if the Simpson Connector is adequate for the intended application.