

# CONSTRUCTION SCREWS



Steeler Construction Screws are produced in ISO 9001 & ISO 14001 certified environments and meet/exceed one or more of the following ASTM designations: C 954, C 1002, and C 1513.

PRODUCT	PART #	SIZE	QTY	WT	APPLICATIONS & FEATURES
 <b>SUPER STEELERS™</b>	168	#6 x 1"	10M	28.6	<ul style="list-style-type: none"> <li>✓ Ideal for light-gauge steel framing.</li> <li>✓ Easily attach gypsum board to 25ga-20ga steel &amp; steel to steel.</li> <li>✓ Identified by its bugle head with deep recess &amp; sharp point, which minimizes false starts and speeds up the fastening process.</li> <li>✓ Yellow Zinc is designed to slow the formation of rust.</li> </ul>
	268 & 268YZ	#6 x 1-1/8"	10M	30.8	
	368	#6 x 1-1/4"	8M	27.8	
	468 & 468YZ	#6 x 1-5/8"	5M	21.6	
	768	#6 x 2"	5M	26.6	
	868 & 868YZ	#8 x 2-1/4"	4M	22	
	968 & 968YZ	#7 x 2-1/2"	2.5M	19.1	
	1168 & 1168YZ	#8 x 3"	2M	20.2	
	1268 & 1268YZ	#10 x 3-1/2"	1M	18	
	1368 & 1368YZ	#10 x 4"	1M	20.7	
	1568 & 1568YZ	#10 x 5"	1M	24.6	
1768 & 1768YZ	#10 x 6"	1M	29		
 <b>HI-LO SUPER STEELERS™</b>	368HL	#6 x 1-1/4"	8M	30	<ul style="list-style-type: none"> <li>✓ Similar application to the Super Steeler.</li> <li>✓ High-low thread screws faster and gets a better hold, especially in lighter gauges.</li> </ul>
	468HL	#6 x 1-5/8"	5M	24	
	768HL	#6 x 2"	5M	29	
 <b>SUPER FRAMER</b>	23 & 23Z	#7 x 7/16"	15M	37.6	<ul style="list-style-type: none"> <li>✓ Made for framing 25ga-20ga steel to steel.</li> <li>✓ Identified by its deep recess &amp; sharp point.</li> </ul>
 <b>SUPER LATHERS</b>	31 & 31Z	#8 x 9/16"	10M	35.2	<ul style="list-style-type: none"> <li>✓ Designed for metal lath to 25ga-20ga steel.</li> <li>✓ Identified by its wafer head &amp; sharp point.</li> </ul>
	32 & 32Z	#8 x 1"	5M	26.6	
	33 & 33Z	#8 x 1-1/4"	5M	31.2	
 <b>SUPER HEX FRAMERS</b>	25AZ	#8 x 1/2"	10M	29.3	<ul style="list-style-type: none"> <li>✓ Made for multipurpose sheet metal and HVAC work. Great for framing 25ga-20ga steel or attaching siding &amp; awning to wood.</li> <li>✓ Identified by its hex washer head &amp; sharp point.</li> </ul>
	25BZ	#8 x 3/4"	10M	37	
	25CZ	#8 x 1"	8M	37.9	
	25DZ	#8 x 1-1/4"	5M	27.9	
	25EZ	#8 x 1-1/2"	5M	32.3	
	HWH14-1	#14 x 1"	4M	55.5	
	HWH14-114	#14 x 1-1/4"	4M	55.5	
 <b>SUPER WOODIES™</b>	100 & 100YZ	#6 x 1"	10M	28.6	<ul style="list-style-type: none"> <li>✓ Manufactured for fastening (up to) multiple layers of gypsum board or similar materials to wood.</li> <li>✓ Identified by its bugle head, coarse thread, sharp point &amp; deep recess.</li> </ul>
	200 & 200YZ	#6 x 1-1/8"	10M	30.8	
	300 & 300YZ	#6 x 1-1/4"	8M	27.8	
	400 & 400YZ	#6 x 1-5/8"	5M	21.6	
	700 & 700YZ	#6 x 2"	5M	26.6	
	800 & 800YZ	#6 x 2-1/4"	4M	22	
	900 & 900YZ	#7 x 2-1/2"	2.5M	19.1	
	1100 & 1100YZ	#8 x 3"	2M	20.2	
	 <b>SUPER LAMINATING</b>	12	#10 x 1-1/2"	5M	
 <b>RUST RESISTANT SCREWS</b>	300R1K	#6 x 1-1/4"	8M	27.8	<ul style="list-style-type: none"> <li>✓ 300R1K – 1100R1K: coarse thread &amp; sharp point. 14R1K &amp; 16R1K: drill point &amp; bugle head. All rated 1000 hours.</li> <li>✓ 44R2KMAG (wafer head) is best for heavy gauge applications and is rated 2000 hours.</li> <li>✓ Designed for fastening exterior sheathing and high moisture areas.</li> <li>✓ Identified by gray ruspert coating &amp; deep recess for fast drill time.</li> </ul>
	400R1K	#6 x 1-5/8"	5M	17.4	
	700R1K	#7 x 2"	5M	17.4	
	900R1K	#8 x 2-1/2"	2.5M	8.7	
	1100R1K	#8 x 3"	2M	7	
	14R1K	#6 x 1-1/4"	8M	31.8	
	16R1K	#7 x 1-7/8"	4M	31.8	
	44R2KMAG	#10 x 3/4"	5M	30.8	

\*\*"Z" in part number indicates zinc coating version. "YZ" indicates yellow zinc coating.

# CONSTRUCTION SCREWS



Steeler Construction Screws are produced in ISO 9002 & ISO 14001 certified environments and meet/exceed one or more of the following ASTM designations: C 954, C 1002, and C 1513.

PRODUCT	PART #	SIZE	QTY	WT	APPLICATIONS & FEATURES
	13	#6 x 1"	10M	32.6	<ul style="list-style-type: none"> <li>✓ Self-drilling drywall screw.</li> <li>✓ Manufactured for attaching gypsum (up to 5/8") to 20-14ga steel framing.</li> <li>✓ Self-drilling tip makes for faster &amp; easier installation.</li> </ul>
	13.5 & 13.5Z	#6 x 1-1/8"	10M	37.2	
	14 & 14Z	#6 x 1-1/4"	8M	31.8	
	15 & 15Z	#6 x 1-5/8"	5M	25.5	
	16 & 16Z	#6 x 1-7/8"	4M	23.5	
	30S	#8 x 2-3/8"	2M	18.5	
	30M & 30MZ	#8 x 2-5/8"	2M	20	
	30L	#8 x 3"	2M	23.8	
	CB368	#8 x 1-1/4"	5M	19.9	<ul style="list-style-type: none"> <li>✓ Sharp points (368, 468 &amp; 868) are designed for attaching cement board to wood and light-gauge steel (20ga-25ga).</li> <li>✓ Driller tips (14, 15 &amp; 30S) are designed for attaching cement board (up to multiple layers) to wood or to 20ga-14ga steel framing.</li> <li>✓ Identified by bugle head for quicker installation times.</li> </ul>
	CB468	#8 x 1-5/8"	4M	15.9	
	CB868	#8 x 2-1/4"	2M	15.9	
	CB14	#8 x 1-1/4"	5M	19.9	
	CB15	#8 x 1-5/8"	4M	15.9	
	CB30S	#8 x 2-1/4"	2M	8.0	
	19 & 19Z	#7 x 7/16"	15M	39.6	<ul style="list-style-type: none"> <li>✓ Best for fastening 20ga-14ga steel to steel.</li> <li>✓ 19 &amp; 20 identified by pan head.</li> <li>✓ 40 &amp; 41 identified by flat head.</li> <li>✓ Known for its deep recess which quickens drill times.</li> </ul>
	20 & 20Z	#8 x 1/2"	10M	31.9	
	40-12	#10 x 1/2"	10M	46.9	
	41ZSUPER	#10 x 3/4"	5M	59.4	
	34 & 34Z	#8 x 1/2"	10M	36.3	<ul style="list-style-type: none"> <li>✓ Made for attaching metal lath to steel framing up to 12ga.</li> <li>✓ Identified by extra-wide wafer head and driller tip for faster installation.</li> </ul>
	35 & 35Z	#8 x 1"	5M	27.5	
	36 & 36Z	#8 x 1-1/4"	5M	31.9	
	38 SUPER	#8 x 1-3/4"	5M	32.6	
	38Z SUPER	#8 x 1-3/4"	4M	40.0	
	50PZ	#10 x 5/8"	5M	27.5	
	44ZMAG	#10 x 3/4"	5M	30.8	
	26A & 26AZ	#8 x 1/2"	10M	31.9	<ul style="list-style-type: none"> <li>✓ Designed for multi-purpose sheet metal &amp; HVAC work and other steel framing and metal to metal applications.</li> <li>✓ Identified by its hex washer head.</li> <li>✓ Larger sizes are manufactured for heavy-duty steel framing and fastening multiple layers of heavy gauge steel.</li> <li>✓ #4 point (washer): 500 hour rating, zinc + seal coating. #5 point (no washer): 1000 hour rating with silver coating.</li> </ul>
	26BZ	#8 x 3/4"	10M	41.8	
	26CZ	#8 x 1"	8M	39.6	
	26EZ	#8 x 1-1/2"	5M	34.3	
	28AZ	#10 x 1/2"	10M	47.5	
	28BZ	#10 x 3/4"	5M	30.6	
	28CZ	#10 x 1"	5M	56.3	
	HWHTZ10-2	#10 x 2"	2.5M	24.2	
	29BZ	#12 x 3/4"	5M	37.8	
	29CZ	#12 x 1"	3M	29	
	HWHTZ14-114	#14 1-1/4"	2M	34	
HWHT4Z12-114	#12 x 1-1/4"	2M	41		
HWHT5Z12-114	#12 x 1-1/4"	2.5M	51.2		
	RT10-1716	#10 x 1-7/16"	4M	38.3	<ul style="list-style-type: none"> <li>✓ Best for attaching plywood or composite materials to metal.</li> <li>✓ Identified by all reamer TEK head, winged pattern near bottom &amp; zinc coating.</li> </ul>
	RT10-212	#10 x 2-1/2"	1.5M	21.8	
	RT12-2	#12 x 2"	1.5M	24	
	RT12-212	#12 x 2-1/2"	1M	19.8	
	RT12-258	#12 x 2-5/8"	1M	23	
	RT12-234	#12 x 2-3/4"	1M	23.8	

\*"Z" in part number indicates zinc coating version. "YZ" indicates yellow zinc coating.

**For more information, visit [www.steeler.com](http://www.steeler.com)**